

BIG BIKE PARTS® INSTALLATION INSTRUCTIONS

Copyright© 2005 by Big Bike Parts, Inc.® No part of this instruction sheet may be reproduced without the written permission of Big bike Parts, Inc. ®

DUAL FUNCTION LED SPOILER LIGHT GL1800 GOLDWING

PART NO. 10-518 & 10-528

TOOLS NEEDED: PHILLIPS SCREWDRIVER
5MM ALLEN WRENCH
6MM ALLEN WRENCH

INSTALLATION:

1. USING 6MM ALLEN WRENCH REMOVE THE TWO BOLTS HOLDING THE PASSENGER GRAB HANDLES ON EACH SIDE.
2. REMOVE THE SEAT.
3. USING PHILLIPS SCREWDRIVER, REMOVE THE SCREWS ON THE INSIDE OF TRUNK LID AND REMOVE THE TRUNK LID INNER LINER.
4. USING PHILLIPS SCREWDRIVER REMOVE THE TWO SCREWS HOLDING THE OLD SPOILER LIGHT.
5. REMOVE THE OLD SPOILER LIGHT FROM THE SPOILER.
6. RUN THE WIRES FOR THE NEW SPOILER LIGHT INTO THE SPOILER.
7. TIGHTEN THE NEW SPOILER LIGHT TO SPOILER REUSING SCREWS REMOVED IN STEP 4.
8. PLUG THE WHITE TWO- PIN CONNECTOR FROM NEW SPOILER LIGHT INTO THE TWO PIN CONNECTOR BEHIND TRUNK INNER LINER.
9. USING 5MM ALLEN WRENCH REMOVE THE FIVE ALLEN HEAD SCREWS THAT HOLD THE REAR PANEL BETWEEN THE SADDLEBAGS, AND REMOVE THIS PANEL.
10. RUN THE YELLOW WIRE END OF NEW WIRE HARNESS DOWN ON THE OUTSIDE OF TRUNK BEHIND SEAT AND INTO THE BACK OF BIKE. CONNECT TO THE BROWN WIRE FROM THE BLUE THREE PIN CONNECTOR BEHIND REAR FENDER.
11. CHECK TO MAKE SURE THE SPOILER LIGHT NOW FUNCTIONS AS A RUNNING AND BRAKE LIGHT, AND THAT ALL OTHER LIGHTS STILL FUNCTION PROPERLY.
12. REINSTALL ALL REMOVED PARTS IN THE REVERSE OF REMOVAL.