

BIG BIKE PARTS®

INSTALLATION INSTRUCTIONS

LAMPGARD™
PART NO. 52-699

FOR HONDA
GL1800 GW

Copyright© 2003 by Big Bike Parts, Inc. No part of this instruction sheet may be reproduced without the written permission of Big Bike Parts, Inc.

1. CLEAN THE HEADLIGHT AND THE NEW LAMPGARD WITH RUBBING ALCOHOL.
2. PLACE FOUR OF THE DUAL LOCK FASTENERS ON THE LAMPGARD. (SEE SKETCH BELOW FOR APPROXIMATE PLACEMENT.)
3. PLACE THE MATES FOR THE DUAL LOCK FASTENER TO THE ONES ON THE LAMPGARD. (NOTE: THESE DUAL LOCKS MATE TO EACH OTHER.)
4. PLACE THE LAMPGARD ON THE HEADLIGHT SO THE DUAL LOCK FASTENERS STICK TO THE HEADLIGHT. ONCE IN PLACE, REMOVE THE LAMPGARD LEAVING THE MATE OF THE DUAL LOCK FASTENERS ON THE HEADLIGHT AND THE OTHER MATE ON THE LAMPGARD. THE DUAL LOCK FASTENERS NEED TO SIT ON THE LAMPGARD AND ON THE BIKE FOR 24 HOURS BEFORE EXPOSED TO WEATHER OR LOAD FOR PROPER ADHESION OF THE TAPE.

PLACEMENT OF
DUAL LOCK FASTENERS

