

BIG BIKE PARTS® INSTALLATION INSTRUCTIONS

Copyright© 2009 by Big Bike Parts, Inc. No part of this instruction sheet may be reproduced without the written permission of Big Bike Parts, Inc.

PART NO. 55-148

ABS NECK COVER
HONDA VTX1800

6/18/2009

TOOLS NEEDED: 4MM ALLEN WRENCH 12MM WRENCH PHILLIPS SCREWDRIVER

NOTE: TWO PEOPLE ARE NEEDED FOR INSTALLATION OF THIS PART. THE SEAT NEEDS TO BE REMOVED AND THE TANK PULLED BACK TO INSTALL THIS PART. THIS IS NECESSARY TO ALLOW EASY ACCESS TO THE NECK COVER SCREWS.

INSTRUCTIONS:

1. USING A WRENCH, REMOVE THE PASSENGER SEAT AND THE DRIVER SEAT.
2. USING A 12MM WRENCH, REMOVE THE BOLT AT THE BASE OF THE TANK THAT HOLDS THE TANK ON. NOW PULL THE TANK BACK TO ACCESS THE NECK COVER. HAVE THE OTHER PERSON HOLD THE TANK SO IT DOES NOT FALL.
3. INSTALL THE NEW NECK COVER BY HOLDING EACH HALF AROUND THE FRAME. ALIGN THE ALIGNMENT TABS ON THE TOP OF THE LEFT SIDE COVER INTO THE SLOT ON THE RIGHT SIDE COVER, THEN SEAT THE TOP BOSSES INTO THE GROMMETS AND PUSH EACH OF THE SIDE BOSSES INTO THE SIDE GROMMETS.
4. FINISH INSTALLING THE NECK COVER BY SECURING IT WITH THE HARDWARE PROVIDED.
5. REINSTALL THE TANK AND SEAT IN THE REVERSE OF REMOVAL.